

Swivel Joints

Styles and Dimensions - 2004 / 2833 / 2815 / 3885

Model 2004 Swivel Joint - Tolerances according to ASME B.16.5 and ASME B.16.9													
DN		A		B				C				D	
		PN16	ANSI 150	PN16		ANSI 150		PN16		ANSI 150			
				SR	LR	SR	LR	SR	LR	SR	LR	SR	LR
3"	80	195	235	221	259	241	279	128	166	148	186	247	324
4"	100	203	251	253	299	277	303	156	206	180	230	302	404

Model 2833 Swivel Joint - Tolerances according to ASME B.16.5 and ASME B.16.9													
DN		A		B				C				D	
		PN16	ANSI 150	PN16		ANSI 150		PN16		ANSI 150			
				SR	LR	SR	LR	SR	LR	SR	LR	SR	LR
1.5"	40	214	254	/	229	/	249	/	101	/	121	/	244
2"	50	223	260	/	254	/	273	/	123	/	142	/	285
3"	80	260	300	285	324	305	344	128	166	148	186	312	386
4"	100	276	324	326	376	350	400	156	206	180	230	375	477
6"	150	329	397	426	506	460	537	209	286	243	320	524	676
8"	200	363	442	504	606	544	646	267	369	307	409	645	849
10"	250	394	457	578	705	610	737	326	453	358	485	762	1016
12"	300	410	483	637	789	673	825	385	537	421	573	864	1168

Model 2815 Swivel Joint - Tolerances according to ASME B.16.5 and ASME B.16.9													
DN		A		B				C				D	
		PN16	ANSI 150	PN16		ANSI 150		PN16		ANSI 150			
				SR	LR	SR	LR	SR	LR	SR	LR	SR	LR
1.5"	40	214	254	/	229	/	249	/	101	/	121	/	244
2"	50	223	260	/	254	/	273	/	123	/	142	/	285
3"	80	256	296	283	321	302	341	128	166	148	186	309	385
4"	100	274	322	324	375	348	398	156	206	180	230	373	475
6"	150	329	426	426	503	460	537	209	286	243	320	524	676

Model 3885 Swivel Joint - Tolerances according to ASME B.16.5 and ASME B.16.9													
DN		A		B				C				D	
		PN16	ANSI 150	PN16		ANSI 150		PN16		ANSI 150			
				SR	LR	SR	LR	SR	LR	SR	LR	SR	LR
2"	50	247	284	/	278	/	296	/	123	/	141	/	309
3"	80	289	329	315	353	335	373	128	166	148	186	341	418
4"	100	297	345	347	398	371	422	156	206	180	230	396	498