

# Secondary Compression Plate Seal "L" (CPL5)

## General Information:

The secondary seal is a rim-mounted system suitable for floating roof tanks of all sizes storing all grades of crude and refined products.

## Design Features:

The CPL5 Seal is designed to be installed whilst the tank is in service. The seal incorporates a compression plate, a synthetic rubber wiper and a vapour barrier membrane.

The compression plate can be made from either galvanised steel or stainless steel.

The vapour barrier membrane is normally manufactured from polyurethane-coated nylon fabric with very low vapour permeability properties. PVC, nitrile, PTFE/Teflon or firestop materials may be adopted depending on customers' requirements.

The seal design is such that all the fixings are on the outside of the seal; i.e. the tank shell side is completely smooth. The smooth outer surface of the seal ensures that the risk of damage is minimised if the roof is floating above the tank shell.

The seal can be fixed to either a vertical upstand or horizontal angle. The dimensions of the compression plate can be varied to suit a wide range of nominal rim spaces. The wiper maintains approximately 65 mm contact with the wall of annular spaces.

A double-seal version (DL5) of this design is also available.

## Vapour Membrane:

We recommend the following materials for membrane:

- **Calcium Silicate:** 1.90mm thick. It complies with DIN 22118, DIN 22100 (Part 1) and the Health and Safety Committee Guide of Shell. Meets the LASTFIRE 6.1 specifications. They are 85% compatible with aromatic products.
- **PTFE (Teflon):** 0.25 and 0.35mm thick. They comply with DIN 22118 and DIN 22100 (Part 1). Meets the LASTFIRE 6.1 specifications. They are 100% compatible with aromatic products.
- **Polyurethane (PU):** 0.4 and 0.9 mm thick. They are 100% compatible with aromatic products.
- **Viton:** 1.0mm thick. They are 100% compatible with aromatic products.



## Technical Data

**Rim space:** 200mm ± 100mm (Standard)

**Aromatic resistance:** 100%

## Material Specification

**Compression plate:** 1.6mm Galvanised Steel  
1.5 mm Stainless Steel

**Clamp channels:** Galvanised or Stainless Steel

**Wiper:** Synthetic rubber, high tensile strength, good wear resistance, excellent weathering

**Vapour barrier:** CS, PTFE, Polyurethane, Viton

**Shunts:** Stainless Steel